CHLORINATED PARAFFIN

Clear light pale yellow viscous liquid formalized for use in wide range of industrial applications including flame retardants and plasticizers.

CHLOROPARAFFIN - LV SERIES

PROPERTY	UNIT	TEST METHOD	Specifications
SPECIFIC GRAVITY (AT 27°C)	-	IS 14426 : 1997	1.10 ± 1.50
COLOUR	HAZEN	IS 9591 : 1996	20-30 Max
VOLATILE LOSS (AT 130°C FOR 3 HRS)	%	IS 14426 : 1997	2.0-7.0
CHLORINE CONTENT	%	IS 14426 : 1997	44± 70
FREE MINERAL ACIDITY	%	IS 14426 : 1997	0.01
VISCOSITY (AT 27°C) BROOKFIELD VISCOMETER	POISE	IS 3944 : 1982	0.5 - 700
HEAT STABILITY (AT 180°C FOR 30 MIN.)	COLOUR	IS 14426 : 1997	Light Yellow
THERMAL STABILITY (AT 175°C FOR 4 HRS)	%	IS 14426 : 1997	0.10
CARBON CHAIN	%	-	10 - 14
pH VALUE	-	-	6.0

RECOMMENDED APPLICATIONS

- PVC compounding
- Rexine cloth
- Flexible pipe
- PVC profile
- Vinyl Flooring
- PVC film
- Footwear
- Paint & oil
- Gear oil

PACKAGING

² 03 . I E¦Q FBNC BARREL OR LOOSE IN TANKER

Shelf Life

² 24 Months under recommended condition

Safety

² Refer to Material Safety Data Sheet (MSDS)

Block A - 326 (A,B & C) Matasya Industrial Area, Alwar - 301001 (Rajasthan)
Ph. No. : 0144 - 2338349 | Mob. : +91 86969 00246
www.hindustanchemical.com @ info@hindustanchemical.com

HIND Paraffins