Solvent Reffinate C7 Plus

premium-grade hydrocarbon solvent offering excellent solvency, controlled evaporation, and broad industrial applicability across coatings, adhesives, and rubber processing

Reffinate C7

PROPERTY	UNIT	TEST METHOD	Specifications
SPECIFIC GRAVITY (AT 15°C)	g/mL	ASTM D4052	0.785 - 0.816
COLOUR	Saybolt	IS 9591 : 1996	15-20 Max
Sulphur	Wt.ppm	IASTM_D 5453	2500 Max
Flash Point (Abel)	0C	IP 170	38 Min
Initial Boiling Point	0C	ASTM D86	135 Min
Temp At 50Ml Recov	0C	ASTM D86	200 Max
Temp at 95 Ml Recov	0C	ASTM D86	275 Max
ASTM Dist FBP C	0C	ASTM D86	300 Max
Copper Corrosion	NA	ASTM D130	1a
Water Content	wt.%	ASTM D6304	0.5 Max
Aromatic Content	Vol. %	ASTM D6379	20 Max
Residue On Evaporation	wt.%		0.1 Max

RECOMMENDED APPLICATIONS

- Industrial paint thinners
- Industrial enamel formulations
- Solvent-based adhesive manufacturing

PACKAGING

[2] LOOSE IN TANKER

Shelf Life

[2] 24 Months under recommended condition

Safety

[2] Refer to Material Safety Data Sheet (MSDS)

Block A - 326 (A,B & C) Matasya Industrial Area, Alwar - 301001 (Rajasthan)
Ph. No. : 0144 - 2338349 | Mob. : +91 86969 00246
www.hindustanchemical.com @ info@hindustanchemical.com

HIND Paraffins